



## Transporteurs Fixes pour installations de carrières

Largeur mm	Entraxe M	Inclinaison °	Tension service	Passerelle	Puissance KW	Poids KG
500	8	16	TS20 20+10	NON	7,5	1600
500	10	16	TS20 20+10	NON	7,5	2000
500	12	16	TS20 20+10	NON	7,5	2200
500	14	16	TS20 20+10	NON	7,5	2350
500	16	16	TS20 20+10	NON	7,5	2450
500	18	16	TS20 20+10	NON	7,5	2550
500	20	16	TS20 20+10	NON	7,5	2700
500	22	16	TS20 20+10	NON	7,5	2850
500	24	16	TS20 20+10	NON	7,5	3040
500	26	16	TS20 20+10	NON	7,5	3180
500	28	16	TS20 20+10	NON	7,5	3350
500	30	16	TS20 20+10	OUI	7,5	4620
500	32	16	TS20 20+10	OUI	7,5	4850
500	34	16	TS20 20+10	OUI	7,5	5100

Largeur mm	Entraxe M	Inclinaison °	Tension service	Passerelle	Puissance KW	Poids KG
650	8	16	TS20 20+10	NON	11	1750
650	10	16	TS20 20+10	NON	11	2100
650	12	16	TS20 20+10	NON	11	2540
650	14	16	TS20 20+10	NON	11	2700
650	16	16	TS20 20+10	NON	11	2900
650	18	16	TS20 20+10	NON	11	3280
650	20	16	TS20 20+10	NON	11	3650
650	22	16	TS20 20+10	NON	11	3800
650	24	16	TS20 20+10	NON	11	3980
650	26	20	TS20 40+20	NON	9	4100
650	28	20	TS20 40+20	NON	9	4270
650	30	20	TS20 40+20	OUI	9	5450
650	32	20	TS20 40+20	OUI	9	5680
650	34	20	TS20 40+20	OUI	9	5950

Largeur mm	Entraxe M	Inclinaison °	Tension service	Passerelle	Puissance KW	Poids KG
800	8	18	TS20 20+10	NON	15	1940
800	10	18	TS20 20+10	NON	15	2300
800	12	18	TS20 20+10	NON	15	2850
800	14	18	TS20 20+10	NON	15	3190
800	16	18	TS20 20+10	NON	15	3400
800	18	18	TS20 20+10	NON	15	3650
800	20	18	TS20 20+10	NON	15	3900
800	22	18	TS20 20+10	NON	15	4220
800	24	18	TS20 20+10	NON	15	4500
800	26	18	TS20 20+10	NON	15	4850
800	28	18	TS20 20+10	NON	15	5100
800	30	18	TS20 20+10	NON	15	5380
800	32	18	TS20 20+10	NON	15	5700
800	34	18	TS20 20+10	NON	15	6100

TC 650 x 18M GALVANISE



TC 650 x 180M GALVANISE EN TREILLIS



TC 800x20M CAPOTE

